



### Typical System Application

The **Model SD-660-6** Series Vibration test system is a versatile wide frequency band electro-dynamics vibration test system. It is designed to test from small to medium sized payload such as electronic assemblies and design features meet the testing requirements of the automotive, aviation, military, medical and electronic manufacturing industries, too.

The model is capable of a **Random RMS force of 300 kgf and Sine Vector force rating of 300 kgf** in the frequency of DC to 4,000 Hz under controlled conditions. The system consists of a model SD-660-6 shaker and is driven by the Model DA-3 power amplifier and a 0.75 KW cooling blower.

Standard vibration systems consist of an electro-dynamic exciter (the “shaker”), a state-of-the-art air-cooled switching power amplifier with field power supply and a water cooling unit. Optional items including slip tables, head expanders, accelerometers and vibration controller can be added upon request.

### How to select the suitable model

It is critical to consider the size and position of the test article and the total moving mass of the payload as well as the payload’s inertial and overturning moments when selecting a system for your application. It is recommended the force selected should be 1.2 times the theoretical value, to insure appropriate safety margins. For assistance selecting the best system for your needs, please contact our sales representative.

#### ◎ High FRF & Wide UF

Our new shaker design significantly raises the FRF (Fundamental Resonance Frequency) and UF (Useable Frequency) of our long stroke systems and outperforms similar products from other manufacturers.

#### ◎ Reliable Armature

The unique reinforced armature structure design is state-of-the-art, providing increased reliability and unsurpassed performance. Our proprietary armature structure has been re-designed to optimize its rigidity and force transmissibility. Designed for continuous duty and ideal for research & development, production, stress screening and qualification testing, our ruggedized armatures can endure severe vibration and shock forces and extreme temperature conditions.

#### ◎ Efficient Air Cooling

SD-660-6 shaker and DA-3 power amplifier is totally air cooled for easy installation and economical operation.

#### ◎ Cooling Blower Unit

The suitable Cooling blower is ACU751 as below specification.

#### ◎ Air-Isolated Rotating Trunnion

All shakers come standard in a rotating trunnion for easy 90° rotation between the horizontal and vertical test axes. A labor-saving worm wheel is designed for this rotation, which make it friendly for both men and women. Trunnion




are pneumatically isolated (except low force series) providing high stability and allowing for direct mounting onto conventional industrial concrete floors. All shakers are optionally available with an integrated or stand-alone slip table assembly.

◎ **D-Class Switching Amplifier**

Our state-of-art modular switching amplifiers are 100% air-cooled with redundant safety systems and system interlocks insuring performance that is reliable and stable. All amplifiers adopt IGBT power modules of high quality.

◎ **Safety**

Products comply with European tests standards and ISO regulations.



Armature insert pattern

Shaker body

Amplifier

**SD-660-6/DA-3/ACU751**  
**TECHNICAL SPECIFICATIONS**

<i>Shaker specifications</i>			
<i>Sine (Pk)</i>	300kgf (660 lbf)	<i>Table Diameter</i>	150 mm (6")
<i>Random (RMS)</i>	300kgf (660 lbf)	<i>Load Attachment Points (Standard)</i>	13 Stainless Steel Inserts of M8 or 5/16 UNC (option). Bolts circle is 1@0; 6@75mm; 6@125mm..
<i>Shock (Pk)</i>	600 kgf (1,320 lbf)	<i>Degauss Coil</i>	Standard
<i>Usable Frequency</i>	DC to 4,000 Hz	<i>Stray Flux Density @6 inch (152 mm) above table</i>	< 1 mT (10 gauss)
<i>Maximum Displacement (p-p)</i>	38 mm (1.5")	<i>Overall Dimensions</i>	720mmL×590mmD×625mmH (28.3"L×23.2"D×20.4"H)
<i>Maximum Velocity</i>	2 m/s (78.7 in/s)	<i>Vertical Load Support</i>	120 kg (660 lbs)
<i>Maximum Acceleration</i>	100 g	<i>Weight of Shaker (Uncrated)</i>	600 kg (1,320 lbs)
<i>Fundamental Resonance Frequency (Bare table)</i>	3,300 Hz (nom.) +/- 5%	<i>Compressed Air Requirement</i>	0.6 Mpa (87 psi)
<i>Body Suspension Natural Frequency (Thrust Axis)</i>	2.5 Hz		
<i>Armature Effective Nominal Weight</i>	3 kg (6.6 lbs)		

<i>Power Amplifier Specifications</i>		<i>DA-3</i>
<i>Rated Output Capacity</i>	3 KVA	
<i>Signal to Noise Ratio</i>	Greater than 65 dB	
<i>Amplifier Efficiency</i>	Greater than 90%	
<i>Interlock Protection(to prevent the output devices from working outside their specified limits)</i>	●Input Over/Under Voltage ●Logic Fault ●Output Over Voltage/Current ●Control Power ●External ●Shaker Oil Pressure ●Module O/T ●Door Interlock ●Shaker Temp	



<i>Air Cooling Blower ACU751</i>	
<i>Blower Power (Full Load)</i>	0.75 KW
<i>Air Flow Rate</i>	Air Flow: 0.1 m <sup>3</sup> /s (215CFM) Air Pressure: 0.001 Mpa (0.15psi)

<i>System Environmental Requirement</i>	
<i>Operating Room Temperature</i>	0 to 45 degree C
<i>Humidity</i>	0 to 85%, non condensing
<i>System Continuous Duty</i>	not less than 7 hours at the full ratings
<i>Power Supply Requirement</i>	380/415/480 VAC, 50/60 Hz, 3Ph, 6.5 kW

<i>SYSTEM OPTIONS</i>	
<ul style="list-style-type: none"> <li>● <i>Slip Table Configuration</i></li> <li>● <i>V-Groove Caster and Rail System</i></li> <li>● <i>Remote Control</i></li> <li>● <i>Head Expander</i></li> </ul>	<ul style="list-style-type: none"> <li>● <i>Thermal Barrier</i></li> <li>● <i>Load Support Air Compensator</i></li> <li>● <i>Air Caster</i></li> </ul>

All the features make the SD-660-6/DA-3/ACU751 a reliable and affordable system for your applications.

NOTE: In keeping with our commitment to continuous product improvement, the information herein is subject to change.